

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 992 921 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
12.04.2000 Bulletin 2000/15

(51) Int Cl.7: **G06F 17/30**(21) Application number: **99307465.7**(22) Date of filing: **21.09.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Griffith, Gary L.**
Arvada, Colorado 80005 (US)

(74) Representative:
Watts, Christopher Malcolm Kelway, Dr. et al
Lucent Technologies (UK) Ltd,
5 Mornington Road
Woodford Green Essex, IG8 0TU (GB)

(30) Priority: **29.09.1998 US 162494**

(71) Applicant: **LUCENT TECHNOLOGIES INC.**
Murray Hill, New Jersey 07974-0636 (US)

(54) Computer access dependent on the location of the accessing terminal

(57) Determining the location of a wireless terminal provides access to data stored in a database of a central computer associated with that location to the wireless terminal. The user of the wireless terminal is not required to perform any activity to gain access to data associated with the location. The degree of access to the data associated with a location is dependent upon the authorization information supplied by the wireless terminal to the central computer after the location of the wireless terminal has been determined. In addition, the wireless terminal may be a computer capable of wireless communication, a wireless PDA, or a wireless tel-

ephone set having display and data entry capabilities. In a first embodiment, a wireless terminal communicates with the central computer via a wireless switching system. The central computer determines the location of the wireless terminal upon establishment of a communication path between the wireless terminal and the central computer. In a second embodiment of the invention, the wireless terminal communicates via a wireless transceiver with the central computer. There is one wireless transceiver for each location. The transceivers are connected to the central computer by a local area network (LAN).




FIG. 1

EP 0 992 921 A2

Description

Technical Field

[0001] The present invention relates to wireless switching systems and, in particular, to providing remote computer access to an accessing terminal based on the location of that terminal.

Background of the Invention

[0002] In the modern commercial environment, there are many situations where it is desirable that computer access to information be based on the location of the terminal requesting that information. For example, when a doctor enters the room of a patient, the doctor wishes to access all records of the patient which are stored in a computer database. Even if the doctor is equipped with a laptop computer or PDA device, the doctor must enter the patient's identification in order to obtain this record. The need to enter the patient's identification is true even if the laptop computer or PDA device is communicating with the database computer via a wireless link. A nurse entering the patient's room also faces the same problem. Whereas, in normal situations, the time required to enter the patient's identification is simply a waste of a valuable resource and an inconvenience. It is possible to function in this manner. However, if an emergency occurs that is life threatening for the patient, there is not time for a doctor or a nurse to be operating a keyboard. Other situations arise in the commercial or military environments where the access to information is time critical.

Summary of the Invention

[0003] The aforementioned problems are solved and a technical advance is achieved in the art by an apparatus and method that determines the location of a wireless terminal and provides access to data stored in a database of a central computer associated with that location to the wireless terminal. The user of the wireless terminal is not required to perform any activity to gain access to data associated with the location. Advantageously, the degree of access to the data associated with a location is dependent upon the authorization information supplied by the wireless terminal to the central computer after the location of the wireless terminal has been determined. In addition, the wireless terminal may be a computer capable of wireless communication, a wireless PDA, or a wireless telephone set having display and data entry capabilities.

[0004] In a first embodiment, a wireless terminal communicates with the central computer via a wireless switching system. The central computer determines the location of the wireless terminal upon establishment of a communication path between the wireless terminal and the central computer. In a second embodiment of

the invention, the wireless terminal communicates via a wireless transceiver with the central computer. There is one wireless transceiver for each location. The transceivers are connected to the central computer advantageously by a local area network (LAN).

[0005] Other and further aspects of the present invention will become apparent during the course of the following description by reference to the accompanying drawing.

Brief Description of the Drawing

[0006]

FIG. 1 illustrates, in block diagram form, a system for implementing the first embodiment of the invention;
 FIG. 2 illustrates, in block diagram form, a system for implementing the second embodiment of the invention;
 FIGS. 3 and 4 illustrate tables and a database utilized by a central computer;
 FIGS. 5 and 6 illustrate, in flow chart form, steps performed by a central computer in a first implementation of the invention;
 FIG. 7 illustrates, in block diagram form, a fixed unit;
 FIG. 8 illustrates, in block diagram form, a wireless telephone;
 FIG. 9 illustrates, in flow chart form, steps performed by a wireless terminal;
 FIG. 10 illustrates, in block diagram form, steps performed by a fixed unit;
 FIG. 11 illustrates, in flow chart form, steps performed by a central computer in a second implementation of the invention;
 FIG. 12 illustrates, in block diagram form, a transceiver;
 FIG. 13 illustrates, in block diagram form, a laptop computer configured as a wireless terminal;
 FIG. 14 illustrates a table for utilization by a central computer; and
 FIG. 15 illustrates a table and database for utilization by a central computer.

Detailed Description

[0007] FIG. 1 illustrates, in block diagram form, a first embodiment of the invention. Wireless terminals 112-114 are interconnected to central computer 119 via base stations 121-122 and wireless switching system 111. In FIG. 1, when a wireless terminal enters a new location, it receives the identification of the fixed unit providing coverage for that location. The wireless terminal is responsive to the identification information from the fixed unit received via a transmission media other than that used by wireless switching system 111 to establish a data communication path to central computer 119 via a base station and wireless switching system

111. The wireless terminal then transmits to central computer 119 the identification information of the fixed unit. In response, central computer 119 determines the data that is assigned to that location. Central computer 119 then obtains the identification information of the wireless terminal. Central computer 119 determines what portion of the data assigned to the location can be accessed by the wireless terminal based on the identity of the wireless terminal. This portion of the data is referred to as authorized data. Central computer 119 is then responsive to requests from the wireless terminal to give the wireless terminal access to the authorized data. In addition, the wireless terminal can update portions of authorized data by the transmission of messages to central computer 119. If the system illustrated in FIG. 1 is serving a hospital, a doctor walking into a patient's room would have full access to the patient's records stored in central computer 119. However, a nurse would be given access only to a portion of the patient's records stored on central computer 119.

[0008] The wireless terminals may be laptop computers with a wireless interface designed to function with wireless switching system 111, PDAs similarly equipped, or wireless telephone sets. In addition, the transfer of data from central computer 119 to a wireless terminal may be in the form of text, video, or audio formats. For example, an individual delivering supplies or food to a patient in a hospital may only need to know the name of the patient. In such a situation, a wireless telephone would be very adequate for receiving audio information defining the name of the patient.

[0009] One skilled in the art could readily see that other methods could be utilized to determine the location of a wireless terminal. For example, the wireless terminals could transmit identification information defining the wireless terminal to a fixed unit which then could relay this to central computer 119 via wired or wireless media to central computer 119. In addition, global positioning satellite (GPS) devices or base stations could be used to determine a position of a wireless terminal.

[0010] FIG. 2 illustrates, in block diagram form, a second embodiment of the invention. Wireless transceivers 201-206 each provide coverage for an individual location. When wireless terminal 209 enters the area that is covered by transceiver 202, a wireless communication link is established between wireless terminal 209 and wireless transceiver 202. Upon establishment of this link, transceiver 202 communicates via LAN 207 the identity of wireless terminal 209 and the identification information of transceiver 202. Central computer 208 then requests the identification information from wireless terminal 209. Based on the identification information from wireless terminal 209 and the location as defined by the identification of transceiver 202, central computer 208 authorizes access to portions of the data assigned to the location covered by transceiver 202. Wireless terminal 209 then is free to read and write the authorized data.

[0011] Central computer 119 utilizes Table 301 of FIG. 3 to maintain at which location a wireless terminal is. When a wireless terminal changes location, central computer 119 determines this by detecting that the location in FIG. 3 is no longer the real location of the wireless terminal.

[0012] FIG. 4 illustrates database 401 in which data assigned to each location is maintained and Table 402. Table 402 comprises pointers which are constructed based on location pointers into database 401 and the terminals' authorization codes. The terminal authorization codes are determined by central computer 119 based on the location information and the identification information of the wireless terminal.

[0013] FIGS. 5 and 6 illustrate, in flow chart form, the steps performed by central computer 119 in implementing the first embodiment of the invention. Decision block 501 determines if there is a message from a wireless handset. If the answer is no, control is transferred to block 502 which performs normal processing before returning control back to decision block 501. If the answer in decision block 501 is yes, decision block 507 determines if a "no fixed unit" message is being received from a wireless telephone. Such a message indicates that a wireless telephone is not receiving the transmission signal from any fixed unit. If the answer is yes in decision block 507, control is transferred to block 504 which determines the last known location. Central computer 119 maintains a list of last known locations for each of the wireless terminals. Block 506 then signals that the wireless telephone cannot receive a fixed unit around the last location listed for the wireless telephone. This signaling may be in the form of a message displayed to an operator of central computer 119 or merely a message being included in a maintenance log of central computer 119. After execution of block 506, control is transferred back to decision block 501.

[0014] Returning to decision block 507, if the answer is no, decision block 508 determines if a low battery indication was included in the message identifying the fixed unit from the wireless telephone. If the answer is no in decision block 508, block 509 determines the location based on the identification code of the fixed unit of the wireless telephone before transferring control to decision block 601 of FIG. 6. If the answer in decision block 508 is yes, the low battery indication for the identified fixed unit is placed in the database, and a maintenance message indicating low battery is generated before transferring control to block 512. Block 512 performs the same operations as block 509 before transferring control to decision block 601 of FIG. 6.

[0015] Control is transferred to decision block 601 of FIG. 6 from either block 509 or block 512. Decision block 601 determines if the wireless terminal has changed its location. This is performed by utilizing the determined location in comparison with the location given for the terminal in Table 301 of FIG. 3. If the wireless terminal has changed locations, block 608 updates Table 301 (also

referred to as Table 1 in FIG. 6) to reflect this new location, and block 609 requests the identification information from the wireless terminal by a message transmitted via wireless switching system 111. Decision block 611 determines when the identification information is received from the wireless terminal. When the identification information is received, control is transferred to block 612 which determines the authorized access to the location's data that is to be given to the wireless terminal. Block 613 stores this authorized access information into Table 402 of FIG. 4 (also referred to as Table 2 in FIG. 6) before returning control back to decision block 501 of FIG. 5.

[0016] Returning to decision block 601, if the wireless terminal has not changed location, control is transferred to decision block 602 which determines if the wireless terminal is authorized to access information in database 401 of FIG. 4 assigned to the particular location. Decision block 602 makes this determination by determining if there is an entry for the wireless terminal in column 412 of Table 402 of FIG. 4. If the answer is no in decision block 602, control is transferred to error recovery in block 603. If the answer is yes, control is transferred to decision block 604 which determines if the wireless terminal is requesting access to database 401. If the answer is no, control is transferred to block 606. The latter block performs normal processing before returning control back to decision block 501 of FIG. 5. If the answer is yes in decision block 604, block 607 performs the requested access to database 401 utilizing the pointer that comprises an entry from column 409 and an entry from column 411 of Table 402 of FIG. 4 to access the appropriate portion of database 401. After execution of block 607, control is transferred back to decision block 501 of FIG. 5.

[0017] FIG. 7 illustrates in block diagram form a fixed unit. The fixed unit of FIG. 7 is powered by battery 701. However, one skilled in the art could readily see that normal building AC power could also be utilized to power the fixed unit. Controller 703 periodically transmits the identification code for the fixed unit via transmitter 704. Advantageously, transmitter 704 can be transmitting utilizing infrared transmission or ultrasonic transmission. Transmitters for transmitting either infrared or ultrasonic are well known in the art. If controller 703 detects that battery 701 is at a low power level via conductor 707, battery monitor 702, and conductor 708, controller 703 sets alarm indicator 705 and transmits the low power indication along with the identification code via transmitter 704.

[0018] Wireless handset 112 is illustrated in greater detail in FIG. 8. Wireless handset 112 implements a wireless protocol that allows wireless handset 112 to maintain a wireless signal link with wireless telecommunication system controller 111 via base stations 121-122. One air interface that can be used is the Japanese PHS protocol as set forth in "User-Network Interface and Inter-Network Interface Standards for PHS",

the Telecommunication Technology Committee, 1995, and "Personal Handy Phone System RCR Standard", Version 1, RCR STD-28, December 20, 1993. The message set of the PHS protocol is similar to the ISDN message set. Overall control of the wireless handset is provided by control unit 801. Units 802, 803, 806, 807, 808, and 809 provide the RF communication capabilities for the wireless handset. Elements 804, 810, and 811-814 provide the audio information received and transmitted to the user; whereas, elements 816-818 and 805 provide the basic user interface. The PHS protocol allows control unit 801 to establish a logical data channel with system controller 111. Control unit 801 utilizes this logical data channel to transmit identification information for fixed units to system controller 111 which in turn transfers this information to central computer 119 of FIG. 1 using well known methods. Fixed unit receiver 321 receives the identification code of a fixed unit and transfers this identification code to control unit 801 for transmission to central computer 119. Fixed unit receiver 321 is of a design well known in the art for either infrared or ultrasonic transmission media. One skilled in the art could readily see that fixed unit receiver 321 could provide to control unit 801 the signal strength of the received signal. Further, control unit 801 could also tune fixed unit receiver 321 to receive different frequencies or other variations of the transmission media using well known techniques in the art.

[0019] FIG. 9 illustrates the steps performed by a wireless terminal such as wireless handset 113. Decision block 901 determines if the time has elapsed to monitor for a fixed unit. Advantageously, every second the wireless handset monitors to determine if the transmission signal of a fixed unit is being received. If the answer in decision block 901 is no, normal processing is performed by block 902 before control is returned back to decision block 901.

[0020] If the answer in decision block 901 is yes, control is transferred to decision block 903 which determines if a transmission signal is being detected. If the answer in decision block 903 is no, control is transferred to block 904 which establishes a logical channel to central computer 119 via a base station and system controller 111. After the establishment of the logical channel, the wireless handset transmits a "no fixed unit" message to the central computer before transferring control back to decision block 901. Returning to decision block 903, if the answer is yes, control is transferred to block 908 which establishes a logical channel to central computer 119. Block 909 determines the identification code of the fixed unit whose transmission signal is being received, and block 911 transmits the received identification code to central computer 119 before transferring control to decision block 912. Decision block 912 determines if a low battery indication was included in the transmission signal from the fixed unit. If the answer is no, control is transferred back to decision block 901. If the answer in decision block 912 is yes, block 913 transmits a low bat-

tery indication message to central computer 119 for the identified fixed unit.

[0021] FIG. 10 illustrates the steps performed by a fixed unit. Decision block 1001 determines if it is time to transmit the identification code of the fixed unit. Advantageously, the identification code is transmitted every tenth of a second. If the answer is no, control is transferred back to decision block 1001. If the answer is yes, decision block 1003 determines if battery monitor 702 of FIG. 7 is indicating a low battery. If the answer is no, block 1004 simply transmits the identification code of the fixed unit before transferring control back to decision block 1001. If the answer in decision block 1003 is yes, block 1006 transmits a message that includes the identification code and a low battery indication before transferring control back to decision block 1001.

[0022] FIG. 11 illustrates, in flow chart form, the steps performed by central computer 208 in implementing the second embodiment of the invention. Central computer 208 maintains an internal table which specifies the locations of transceivers 201-206. When a message is received from a wireless terminal via one of the transceivers, control is transferred to block 1105. The latter block determines the location of the wireless terminal based on the internal table that specifies the location of the transceiver being utilized by the wireless terminal. The identification of the transceiver is included in each message sent by the transceiver to central computer 208 via LAN 207. After execution of block 1105, control is transferred to block 1101.

[0023] Decision block 1101 determines if the wireless terminal has changed its location. This is performed by utilizing the determined location in comparison with the location given for the terminal in Table 1401 of FIG. 14 (also referred to as Table 1 in FIG. 11). If the wireless terminal has changed locations, block 1108 updates Table 1401 to reflect this new location, and block 1109 requests the identification information from the wireless terminal by a message transmitted via central computer 208. Decision block 1111 determines when the identification information is received from the wireless terminal. When the identification information is received, control is transferred to block 1112 which determines the authorized access to the location's data that is to be given to the wireless terminal. Block 1113 stores this authorized access information into Table 1502 of FIG. 15 (also referred to as Table 2 in FIG. 11) before returning control back to decision block 1100. Returning to decision block 1101, if the wireless terminal has not changed location, control is transferred to decision block 1102 which determines if the wireless terminal is authorized to access information in database 1501 of FIG. 15 assigned to the particular location. Decision block 1102 makes this determination by determining if there is an entry for the wireless terminal in column 1512 of Table 1502 of FIG. 15. If the answer is no in decision block 1102, control is transferred to error recovery in block 1103. If the answer is yes, control is transferred to decision block 1104

which determines if the wireless terminal is requesting access to database 1501. If the answer is no, control is transferred to block 1106. The latter block performs normal processing before returning control back to decision block 1100. If the answer is yes in decision block 1104, block 1107 performs the requested access to database 1501 utilizing the pointer that comprises an entry from column 1509 and an entry from column 1511 of Table 1502 of FIG. 15 to access the appropriate portion of database 1501. After execution of block 1107, control is transferred back to decision block 1100.

[0024] FIG. 12 illustrates, in block diagram form, transceiver 202 of FIG. 2. The other transceivers of FIG. 2 are identical in design. Controller 1201 transmits and receives messages with central computer 208 via LAN interface 1202 and LAN 207. The design of LAN interface 1202 is well known in the art and can be designed to utilize a number of different LAN protocols. Controller 1201 communicates with wireless terminals via infrared (IR) transmitter 1203 and IR receiver 1204. One skilled in the art could readily envision that the transmission medium could be other than infrared such as electromagnetic. Controller 1201 periodically transmits its identification information via IR transmitter 1203 at pre-defined times. When a wireless terminal receives these periodic transmissions, the wireless terminal transmits via IR receiver 1204 the identification of the wireless terminal. Controller 1201 then forms a message consisting of the identification of the wireless terminal and the identification of transceiver 202 and transmits this message via LAN interface 1202 and LAN 207 to central computer 208. Controller 1201 can be communicating with a number of wireless terminals at any given time. This allows a number of wireless terminals to be in the location covered by transceiver 202. Controller 1201 is responsive to messages received from central computer 208 via LAN interface 1202 and LAN 207 to form a message utilizing the wireless terminal identification that was included in the message from central computer 208. This formed message is then transmitted via IR transmitter 1203. The wireless terminals constantly monitor transmissions from controller 1201 and will only respond to those messages which contain the wireless terminal's identification information. This allows central computer 208 to communicate with individual wireless terminals.

[0025] FIG. 13 illustrates, in block diagram form, wireless terminal 112. The other wireless terminals illustrated in FIG. 2 would be similar in design. However, laptop computer 1301 may be replaced with a PDA. Laptop computer 1301 is responsive to the periodic polling message received from a transceiver to transmit back a message defining the identity of wireless terminal 112. Laptop computer 1301 is responsive to messages received from central computer 208 to take the appropriate actions. For example, laptop computer 1301 is responsive to a message from central computer 208 requesting the identification information of laptop computer 1301 to transmit that information to central computer

208. Laptop computer 1301 also is running an application program that requests and utilizes data stored in database 1501 of FIG. 15.

Claims

1. A method for accessing data, comprising the steps of:

assigning (FIG. 4) one of a plurality of data sets (403, 404) to each of a plurality of locations; determining (601, 608) one of the plurality of locations in which a data device (113) is located; identifying (602) one of the plurality of data sets assigned to the determined one of the plurality of locations; and providing (607) access to the data device to the one of the plurality of data sets.

2. The method of claim 1 wherein each of the plurality of data sets comprises subsets of data and the method further comprises the steps of requesting (611) an identification of the data device; and limiting the access of the data device to pre-defined ones of the subset of data of the one of the plurality of data sets based on the identification of the data device.

3. The method of claim 1 or claim 2 wherein the data device is interconnected to a wireless switching system (111) and the step of determining comprises the step of supplying (909, 911) location information by the data device to a database computer (119) via the wireless switching system whereby the location information identifies the one of the plurality of locations.

4. The method of claim 3 wherein the step of supplying comprises the step of receiving (909) the location information from one of a plurality of fixed units by the data device whereby each of the plurality of fixed units is located in one of the plurality of locations.

5. The method of claim 1 or claim 2 wherein the data device is interconnected to a local area network (107) via a wireless connection through one of a plurality of fixed units (202) that is connected to the local area network and the step of determining comprises the step of supplying (1101) location information by the one of the plurality of fixed units to a database computer (119) via the local area network whereby the location information identifies the one of the plurality of locations.

6. The method of claim 5 wherein each of the plurality

of fixed units is located in one of the plurality of locations and is connected to the local area network.

7. The method of claim 5 or 6 wherein the step of identifying the one of the plurality of data sets assigned to the determined one of the plurality of locations is performed in response to the received location information by the database computer.

8. The method of claim 7 wherein the step of providing access to the data device to the one of the plurality of data sets is performed by the database computer via the one of the plurality of fixed units and the local area network.

9. The method of any of the preceding claims wherein the data device is a computer.

10. The method of any of claims 1 to 8 wherein the data device is a PDA.

11. The method of any of claims 1 to 8 wherein the data device is a wireless telephone.

12. An apparatus for accessing data, comprising means arranged to carry out each step of a method as claimed in any of the preceding claims.




FIG. 1




FIG. 2

TABLE 301 ↗

WIRELESS TERMINAL	LOCATION
112	103
113	101
114	104



FIG. 3*FIG. 4*

FIG. 5






FIG. 6




FIG. 7




FIG. 8

FIG. 9




FIG. 10





FIG. 11






FIG. 12





FIG. 13

TABLE 1401

WIRELESS TERMINAL	LOCATION
209	202
211	204
212	206

FIG. 14*FIG. 15*

THIS PAGE BLANK (USPTO)

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 992 921 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
17.01.2001 Bulletin 2001/03

(51) Int Cl.7: G06F 17/30

(43) Date of publication A2:
12.04.2000 Bulletin 2000/15

(21) Application number: 99307465.7

(22) Date of filing: 21.09.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Griffith, Gary L.
Arvada, Colorado 80005 (US)

(74) Representative: Williams, David John et al
Page White & Farrer,
54 Doughty Street
London WC1N 2LS (GB)

(30) Priority: 29.09.1998 US 162494

(71) Applicant: LUCENT TECHNOLOGIES INC.
Murray Hill, New Jersey 07974-0636 (US)

(54) Computer access dependent on the location of the accessing terminal

(57) Determining the location of a wireless terminal provides access to data stored in a database of a central computer associated with that location to the wireless terminal. The user of the wireless terminal is not required to perform any activity to gain access to data associated with the location. The degree of access to the data associated with a location is dependent upon the authorization information supplied by the wireless terminal to the central computer after the location of the wireless terminal has been determined. In addition, the wireless terminal may be a computer capable of wireless communication, a wireless PDA, or a wireless telephone set having display and data entry capabilities. In a first embodiment, a wireless terminal communicates with the central computer via a wireless switching system. The central computer determines the location of the wireless terminal upon establishment of a communication path between the wireless terminal and the central computer. In a second embodiment of the invention, the wireless terminal communicates via a wireless transceiver with the central computer. There is one wireless transceiver for each location. The transceivers are connected to the central computer by a local area network (LAN).




FIG. 1

EP 0 992 921 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 7465

DOCUMENTS CONSIDERED TO BE RELEVANT			Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Category	Citation of document with indication, where appropriate, of relevant passages			
X	US 5 603 054 A (GOLDSTEIN RICHARD J ET AL) 11 February 1997 (1997-02-11) * figures 1,2,9,14 * * column 2, line 20 - column 6, line 52 * * column 10, line 14 - column 10, line 29 * * column 14, line 25 - column 14, line 37 * * column 17, line 61 - column 20, line 12 * * column 22, line 41 - column 23, line 64 *	1-12	G06F17/30	
X	----- FUJINO N ET AL: "MOBILE INFORMATION SERVICE BASED ON MULTI-AGENT ARCHITECTURE" IEICE TRANSACTIONS ON COMMUNICATIONS, JP, INSTITUTE OF ELECTRONICS INFORMATION AND COMM. ENG. TOKYO, vol. E80-B, no. 10, 1 October 1997 (1997-10-01), pages 1401-1406, XP000734533 ISSN: 0916-8516 * page 1401, column 2, line 15 - page 1401, column 2, line 21 * * page 1403, column 2, line 44 - page 1404, column 2, line 11 * * figures *	1,5-10, 12		
X A	----- WO 98 02824 A (MOTOROLA INC) 22 January 1998 (1998-01-22) * page 2, line 24 - page 3, line 2 * * page 3, line 28 - page 4, line 6 * * page 8, line 16 - page 11, line 8 * ----- -/-	1,5 2-12		
The present search report has been drawn up for all claims				
Place of search THE HAGUE		Date of completion of the search 21 November 2000	Examiner Abbing, R	
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document		

EPO FORM 1503 03 82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 7465

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 598 572 A (TANIKOSHI KOICHIRO ET AL) 28 January 1997 (1997-01-28) * abstract * * column 8, line 5 - column 10, line 49 *	1,5	
A	US 4 835 372 A (GRIFFEE RICHARD A ET AL) 30 May 1989 (1989-05-30) * column 2, line 1 - column 6, line 18 *	1-8	
A	EP 0 853 287 A (NOKIA MOBILE PHONES LTD) 15 July 1998 (1998-07-15) * abstract * * figures 1,2 * * claims *	1,5,9-11	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search THE HAGUE		Date of completion of the search 21 November 2000	Examiner Abbing, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C0*)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 7465

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-11-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5603054 A	11-02-1997	US 5555376 A	10-09-1996
		US 5717955 A	10-02-1998
		US 5611050 A	11-03-1997
		US 5544321 A	06-08-1996
WO 9802824 A	22-01-1998	US 5974447 A	26-10-1999
		AU 3408797 A	09-02-1998
		BR 9710723 A	17-08-1999
		CA 2260264 A	22-01-1998
		CN 1230265 A	29-09-1999
		EP 0912946 A	06-05-1999
US 5598572 A	28-01-1997	JP 7262225 A	13-10-1995
		DE 19509836 A	21-09-1995
US 4835372 A	30-05-1989	US 5640301 A	17-06-1997
		US 5179569 A	12-01-1993
		US 5307372 A	26-04-1994
		CA 1261968 A	26-09-1989
		EP 0230458 A	05-08-1987
		JP 63500546 T	25-02-1988
		WO 8700659 A	29-01-1987
EP 0853287 A	15-07-1998	FI 965278 A	01-07-1998
		CA 2225191 A	30-06-1998
		JP 10257100 A	25-09-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)